

It is claimed:

1 1. A bar-shaped lamp comprising:

2 an elongated shaft;

3 a lamp head affixed to one end of said shaft and
4 provided with a light source; and

5 a reversible elongated foot member receivable in said
6 shaft at an opposite end of said shaft and having at a first end
7 of said foot member an elongated spike adapted to be inserted
8 into the ground and at a second end of said foot member an impact
9 tool capable of rupturing a vehicle window.

1 2. The bar-shaped lamp defined in claim 1 wherein said

2 light source includes at least one light-emitting diode.

1 3. The bar-shaped lamp defined in claim 2 wherein said

2 light source includes a plurality of light-emitting diodes.

1 4. The bar-shaped lamp defined in claim 3 wherein said

2 spike and said tool are both conical.

1 5. The bar-shaped lamp defined in claim 4 wherein said
2 spike and said tool have respective apex angles with the apex
3 angle of said spike being less than the apex angle of said tool.

1 6. The bar-shaped lamp defined in claim 5 wherein said
2 foot member has a portion between said spike and said tool which
3 is flush with said shaft and adapted to be inserted into said
4 shaft.

1 7. The bar-shaped lamp defined in claim 6 wherein
2 said portion has a friction fit in said shaft.

1 8. The bar-shaped lamp defined in claim 6 wherein said
2 portion is threaded into said shaft.

1 9. The bar-shaped lamp defined in claim 6, further
2 comprising a connection replaceable securing said lamp head on
3 said shaft.

1 10. The bar-shaped lamp defined in claim 9 wherein
2 said connection is a threaded connection.

1 11. The bar-shaped lamp defined in claim 10 wherein
2 said lamp head comprises a plate, a plurality of light-emitting
3 diodes mounted on said plate and a spiral contact spring
4 resiliently engageable with a battery in said shaft.

1 12. The bar-shaped lamp defined in claim 11, further
2 comprising a cap adapted to receive said tool and threaded onto
3 said foot member.

1 13. The bar-shaped lamp defined in claim 12, further
2 comprising an elongated light-transmitting body affixed to said
3 head and illuminatable thereby.

1 14. The bar-shaped lamp defined in claim 13 wherein
2 said body is a rod of a light-conducting plastic.

1 15. The bar-shaped lamp defined in claim 14 wherein
2 said rod is composed of polymethylmethacrylate and is threadedly
3 connected to said shaft.

1 16. The bar-shaped lamp defined in claim 1 wherein
2 said shaft comprises a battery holder and a compartment
3 dimensioned to receive said spike.

1 17. The bar-shaped lamp defined in claim 16, further
2 comprising a cap adapted to receive said tool and threaded onto
3 said foot member.

1 18. The bar-shaped lamp defined in claim 17, further
2 comprising an elongated light-transmitting of an acrylic resin
3 body affixed to said head and illuminatable thereby.

1 19. The bar-shaped lamp defined in claim 18 wherein
2 said lamp head comprises a plate, a plurality of light-emitting
3 diodes mounted on said plate and a spiral contact spring
4 resiliently engageable with a battery in said shaft.

1 20. The bar-shaped lamp defined in claim 19 wherein
2 said foot member has a portion between said spike and said tool
3 which is flush with said shaft and adapted to be inserted into
4 said shaft.